



2009 Scheduled Maintenance Intervals

Miles (in thousands)	5/25/45/65/85/105/125	15/55/95	35/75/115
Kilometres (in thousands)	8/40/70/100/130/160/200	25/85/145	55/115/175
Engine Oil/Oil Filter – change oil and replace filter	●	●	●
Wiper Blades – check condition and replace if necessary	●	●	●
Wiper/Washer/Headlight Washer – check adjustment and function, add fluid if necessary	●	●	●
Tires and Spare – check for wear and damage, check pressure	●		● 115K only
– check for wear and damage, check pressure and renewal date of tire set (where applicable)		●	● 35K/75K only
Tires – rotate	● 5K only		
Service Reminder Display – reset	●		
Brake System – check for damage, leaks, pad thickness, fluid level	●	●	●
Cooling System – check level, add if necessary		●	●
Exhaust System – check for damage, leaks		●	●
Engine On Board Diagnostics – check fault memory		● A3, A4 Cab, S4, A6, S6, A8, S8 only	● A3, A4 Cab, S4, A6, S6, A8, S8 only
Engine Compartment – check for leaks		●	●
Battery – check and replace if necessary		●	●
Dust and Pollen Filter – replace		●	●
Automatic Transmission and Final Drive – check for leaks		●	●
Manual Transmission and Final Drive – check for leaks		●	●
Haldex Clutch – change oil			● A3, TT only
Front Axle – check for excessive play, check dust seals on ball joints and tie rod ends		● A3, A4 Cab, S4, A6, S6, A8, S8 only	●
Lights – check all lights, check headlight adjustment		● A8, S8 only	● A3, A4 Cab, S4, A6, S6, A8, S8 only
Drive Shaft Boots – check		●	●
Doors – lubricate doors, check straps and hood latch		● A8, S8 only	● Except A8, S8
Spark Plugs – replace at 35,000 miles or 3 years, whichever occurs first. Then, every 40,000 miles or 3 years, whichever occurs first.			● 35K/115K only: A3 3.2L, TT 3.2L, A8 6.0L only
– replace at 55,000 miles or 6 years, whichever occurs first. Then, every 60,000 miles or 6 years, whichever occurs first.		● 55K only: except A3 3.2L, TT 3.2L, A8 6.0L	
– replace at 75,000 miles			● 75K only: A3 3.2L, TT 3.2L, A8 6.0L only
Continuously Variable Transmission (multitronic) – change ATF			●
Power Steering Fluid – check, add if necessary			●
Air Cleaner – clean housing, replace filter element		● 55K only: except Audi Q7 4.2L, A8 6.0L	● 35K only: A8 6.0L only 75K only: Audi Q7 4.2L, A8 6.0L only 115K only: A8 6.0L only
Ribbed V Belt and Tensioner – check condition and replace if necessary		● R8 only	● Audi Q7 3.6L, A8 6.0L, R8 only
Ribbed V Belt – replace			● 75K only: S4 only
– check condition, replace if necessary. Check tension of belt drive with manual tensioner and retension if necessary.			● 75K only: V6 FSI, V6 TFSI (rear belt), 2.0L TFSI, 5.2L FSI, 4.2L FSI
– replace only the V belt for the compressor drive			● 75K only: 3.0T FSI only
Snow Screen for Air Cleaner – clean		● A4, A5, S5 and A6 only	● A4, A5, S5 and A6 only
Underbody – check for damage and leaks		●	●
Road Test – check braking, kick-down, steering, electrical, heating and ventilation systems, air conditioning, ASL Automatic Shift Lock and power accessories		●	●
Rear Lid Hinges – lubricate		● A8, S8 only	● A8, S8 only
Horn – check function		●	●
Brake Discs – check thickness			●
Lights – check all lights via instrument cluster. Check license plate light from the rear of the vehicle			● Audi Q7, A4 (B8 only), S4, Audi Q5, TT, A5, S5, R8 only
Interior Lights – check all interior lights, glove box illumination, control lights and MMI (if applicable)			●
DSG/S Tronic – change oil and replace filter element			● A3, TT only
AdBlue Fluid – fill completely with fresh fluid (23 liters)	● Audi Q7 3.0L TDI only	● Audi Q7 3.0L TDI only	● Audi Q7 3.0L TDI only
Fuel Filter – remove water		● Audi Q7 3.0L TDI only	
– replace			● Audi Q7 3.0L TDI only
Diesel Particulate Filter (DPF) – check ash content within the DPF. Replace DPF with an ash content greater than or equal to .46 liters.	● 125K only: Audi Q7 3.0L TDI only		
Plenum Panel – clean if dirty (except A3, Audi Q5)		●	●

At 110k miles (175 km) replace timing belt on Audi TT 2.0T with front wheel drive and A4 Cabriolet 2.0T only. Check condition of timing belt tensioning system, dampening pulleys, and idler pulleys and replace if necessary (Audi TT 2.0T with front wheel drive and A4 Cabriolet 2.0T only).
 Brake Fluid – replace every 2 years regardless of mileage.
 Cloth Top – check function and rollover protection every 2 years regardless of mileage (Audi A4/S4 Cabriolet only).